

1. PRODUCT NAME

DynaFill

2. MANUFACTURER

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241

Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com

- **Convenient:** DynaFill is ready-to-use and easy to apply. No mixing required.
- **Solid Foundation:** This polymer fortified emulsion reinforced with fine aggregate provides an ideal base for all Dynaflex Sports Surfacing products.
- **High Polymer Content:** Ensures greater bonding, durability and flexibility.
- **High Solids Formula:** High elastomeric content minimizes shrinkage in deep and/or wide cracks.
- **Fast Drying:** Repair surface imperfections in less time

3. PRODUCT DESCRIPTION

DynaFill is a blend of high molecular weight acrylic polymer, fine ceramic aggregate, surfactants and wetting agents designed to fill cracks on asphalt and concrete surfaces.

Packaging:

Available in 2 gal. pails.

Color:

DynaFill dries to a yellow beige.

Basic Uses:

DynaFill is designed as a crack filler for large cracks or minor depressions. It can also be used as a mastic surface treatment for alligatored areas on asphalt pavements.

Composition:

As shipped, DynaFill is a water-based blend of acrylic polymer and fine graded ceramic aggregate.

Limitations:

Do not allow to freeze. Do not store in direct sunlight or where temperature exceeds 120 F. Do not apply if rain is imminent..

4. INSTALLATION

Preparatory Work:

Crack must be dry, clean, and free of dust and loose material.

Methods:

Spreadable with trowel or squeegee.

Mix Design:

DynaFill is ready-to-use. No heating or dilution is required. Stir well prior to use.

Application:

For filling deep cracks or minor depressions, a second application may be required as some shrinkage can occur. Allow a minimum of 4 hours between applications.

Precautions:

Keep out of reach of children. Container should be closed when not in use. Contains petroleum distillates. Avoid breathing vapor or prolonged contact with skin or eyes. Flush immediately with water. Consult specific Neyra safety data sheets before use.

5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

6. TECHNICAL DATA

Environmental Considerations:

DynaFill is considered nonhazardous when tested according to the EPA's TCLP (Toxicity characteristic Leaching Procedure). DynaFill is a water-based material containing less than 5 g/L (0.08 lbs. / gal.) VOC Content

7. TECHNICAL SERVICE

Material safety data sheets, product and application recommendations, as well as assistance with special situations

and field service are available upon request.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, equipment and workmanship are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of asphalt pavement maintenance and recreational surface products as well as application equipment sold and distributed nationally at our plants and through distributors. To find the supplier most convenient to you, please contact us.

NEYRA Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241
Phone: 513-733-1000
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com